

## Selection of Ammonia (NH3) Sensors

SemeaTech manufactures a number of ammonia (NH3) sensors using different electrochemical (EC) technologies. This document highlights the different sensors and provides recommendations for the selection of these sensors in accordance with user applications.

- Distinctive performances

NH3 Sensor Family	Expected Capacity ppm-hrs	Expected Lifetime years	Typical T90 seconds	Typical Resolution ppm	Notes
Standard 4-series NH3 sensors	>12,000	2	<45	>0.10	The actual lifetime varies based on the ammonia concentration the sensor has exposure to
Standard 7-series NH3 sensors	>12,000	2	<45	>0.30	The actual lifetime varies based on the ammonia concentration the sensor has exposure to
Long-life 4-series NH3 sensors	Non-depleting	5	<90	>0.20	
Long-life 7-series NH3 sensors	Non-depleting	5	<90	>0.30	
4-electrode NH3 sensor	Non-depleting	5	<120	>0.06	It is designed specifically for air quality monitoring (AQM)

- The response time (T90) of an NH3 sensor for less than 45 seconds is essential to meet a variety of regional ammonia safety standards.
- The long-life NH3 sensors are non-depleting regardless of how much ammonia these sensors have been exposed to. The long-life NH3 sensors are ideal to be used in places where ammonia could present 24/7, such as refrigeration facilities or livestock farms.
- The 4-electrode NH3 sensor is designed based on 7-series platform with an additional electrode, Auxiliary. It provides the highest resolution at 60 ppb and outstanding long-term stability.
- SemeaTech offers Smart Modules to pair with these sensors. The Smart Modules provide UART and I2C outputs with a compensation mechanism for environmental parameter fluctuations.

